

AQUADRY 28

AQUADRY 28 Cod. 01219



Design by King & Miranda

FEATURES

- Dehumidification capacity: 28 l/24h*
- Tank capacity: 3.5 l
- Digital control
- LCD Display
- Full tank alarm
- Constant condensation disposal
- Electronic defrosting device
- Hidden tank with push-pull closing panel
- Water tank with handle, for easier transport and emptying
- Visible water level
- Hidden handle
- Wheels
- Cable winder
- Maximum volume of dehumidification: 240 m³



PURE SYSTEM 3

Triple filtration system which combines the filter with activated carbons (eliminates odors and deactivates any potentially harmful gases)
HEPA filter (retains fine dust with a few microns diameter)
Photo catalytic filter (sterilizes air by eliminating a high percentage of viruses and bacteria).



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode; moreover, Aquaria is equipped with back-lit LCD display to view humidity level and ambient temperature.



* (32° C – 80 %RH)

		AQUADRY 28
	Code	01219
	EAN	8021183012194
Dehumidification capacity (1)	l/24h	15
Dehumidification capacity (2)	l/24h	28
Humidifiable Area	m ³	240
Heating power	W	-
Power consumption in dehumidification (1)	W	425
Max Power consumption in dehumidification (2)	W	510
Max Power consumption in dehumidification + heating (2)	W	-
Fan speed		1
Tank capacity	l	3,5
Air flow rate (max)	m ³ /h	285
Dimensions (Width x H x Depth)	mm	280 x 545 x 385
Sound level	db(A)	42
Weight	Kg	18
Refrigerant gas / Charge / GWP*	Type / kg	R134A / 0,160 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Minimum/maximum power supply voltage	V	207 / 264
Air filter		✓
Active carbon filter		✓
Fotocathalitic filter		✓
HEPA filter		✓
Operation with continuous drain		✓
Mechanical controls		
Electronic controls		✓
Mechanical Humidostat		
Digital Humidostat		✓
LCD Display		✓
Backlight LED Display		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Tank full light		✓
Defrosting device		✓
Mot gas defrosting system		
Dehumidifying + heating function (with electrical resistance)		
Handle		✓
Wheels		✓
Tank with push-pull locking		✓
Tank with handle		✓
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)

*hermetically sealed equipment containing fluorinated gas GWP 1430