

# AQUARIA 10

AQUARIA 10 Cod. 01298



## FEATURES

Dehumidification capacity: 10 l/24h\*  
Tank capacity: 1.1 l  
Sound power: 36 dB (A)  
Humidification level adjustable with mechanic humidistat  
Full tank alarm  
Constant condensation disposal  
Defrosting device  
Transparent tank: visible water level  
Handle  
Maximum volume of dehumidification: 90 m<sup>3</sup>



### SILENT SYSTEM

AquaAria 10 is proved to be one of the quietest dehumidifiers in its category, up to 10%\*\* quieter with just  36 dB (A) \*\*



### QUICK CONTROL

Mechanic control, extremely easy to use, to adjust ambient humidity.



### DOUBLE FRAME

Structural robustness and product solidity are made possible by a system of two overlapping frames, that contain the inside elements, protecting them from collisions.



### COMPACT TECHNOLOGY

In just 30 x 25 cm, a dehumidification capacity of 10 l/24h.



\* (32° C – 80 %RH)

\*\* Internal tests on the range Olimpia Splendid

		AQUARIA 10
	Code	01298
	EAN	8021183012989
Dehumidification capacity (1)	l/24h	5,1
Dehumidification capacity (2)	l/24h	10
Humidifiable Area	m <sup>3</sup>	90
Heating power	W	-
Power consumption in dehumidification (1)	W	172
Max Power consumption in dehumidification (2)	W	214
Max Power consumption in dehumidification + heating (2)	W	-
Fan speed		1
Tank capacity	l	1,1
Air flow rate ( max )	m <sup>3</sup> /h	70
Dimensions (Width x H x Depth)	mm	300 x 365 x 255
Sound level	db(A)	36
Weight	Kg	9,5
Refrigerant gas / Charge /GWP*	Type / kg	R134A / 0,075 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Minimum/maximum power supply voltage	V	216/244
Air filter		✓
Active carbon filter		
Fotocathalitic filter		
HEPA filter		
Operation with continuous drain		✓
Mechanical controls		✓
Electronic controls		
Mechanical Humidostat		✓
Digital Humidostat		
LCD Display		
Backlight LED Display		
Indoor humidity visualizer		
Indoor temperature visualizer		
Tank full light		✓
Defrosting device		✓
Mot gas defrosting system		
Dehumidifying + heating function (with electrical resistance)		
Handle		✓
Wheels		
Tank with push-pull locking		
Tank with handle		
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C ( 27°C - 60% RH )

(2) DB 32°C - WB 29°C ( 32°C - 80% RH )

\*hermetically sealed equipment containing fluorinated gas GWP 1430