


UNICO® twin

The system without outdoor unit to air condition two rooms at the same time. Two inside units, the traditional UNICO unit and the UNICO WALL unit, are connected by a refrigerating circuit.

MASTER Cod. 01273

WALL Cod. 01274



Design by King & Miranda



Unico Twin® is the winner of GOOD DESIGN AWARD 2013. Founded in Chicago in 1950, GOOD DESIGN is the oldest internationally recognized competition for design excellence.

FUNCTIONS

- 🌀 **Fan only mode**
- 💧 **Dehumidification only mode**
- 🌡️ **Auto mode:** changes parameters depending on ambient temperature.
- 🌙 **Sleep mode:** gradually increases the temperature set and ensures reduced noise for greater wellbeing at night.

FEATURES of the system

Independent or combined mode: if you choose simultaneous mode
the two units share the power available *
Available in versions: HP (Heat pump)
Doble class **A**
Refrigerant gas R410A**
Multifunction double remote control
24h Timer

MASTER features

Cooling capacity: 2.6 kW
HP mode capacity (heat pump): 2.5 kW
Installation versatility: top or bottom wall installation
Possible glass installation*
Easy installation: Unico Twin can be installed from the inside in a few minutes
Large flap for a homogeneous diffusion of the air in the environment

wall FEATURES

Cooling capacity: 2.5 kW
HP mode capacity (heat pump): 2.2 kW
Maximum silence: up to 25% quieter than the master unit
Available in two colors: pearl and silver



TWIN TECHNOLOGY

Thanks to TWIN® technology double room conditioning is performed in total aesthetic integration with the building, with a considerable simplification of design. Twin® technology allows the use of the two units (Master unit and Wall unit) simultaneously or separately depending on requirements, both in heating and cooling mode.



HEAT PUMP

Heat pump air conditioner. Thanks to this feature you can replace traditional heating in intermediate seasons or support it.



PURE SYSTEM 2

A multi filtering system that combines an electrostatic filter(which eliminates small particles such as smoke, dust, pollen and pet hair, helping to prevent allergic reactions) with an activated carbon filter (which eliminates bad odors and inactivates any harmful gas).

Installation note

By maintaining the same center to center distance of inlet and outlet holes, Unique Twin Master can easily substitute previously installed Unico models.



* During simultaneous operation the inside units are forced at minimum speed.
** hermetically sealed equipment containing fluorinated gas with GWP equivalent 2088

				UNICO TWIN MASTER	
Product code				01273	
Nominal cooling capacity (1)	Pnom.	KW	❄️ 2,6		
Nominal heating capacity (1)	Pnom.	KW	🔥 2,5		
Nominal power consumption for cooling (1)	PEER	KW	0,9		
Nominal absorption for cooling (1)		A	4,3		
Nominal power consumption for heating (1)	PCOP	KW	0,8		
Nominal absorption for heating (1)		A	3,5		
Nominal energy efficiency index (1)	EERd		2,7		
Nominal efficiency coefficient (1)	COPd		3,1		
Energy efficiency class in cooling (1)			A		
Energy efficiency class in heating (1)			A		
Energy consumption in "thermostat off" mode	PTO	W	14,0		
Energy consumption in "standby" mode (EN 62301)	PSB	W	1,0		
Energy consumption for double pipe appliances (1) cooling function	QDD	kWh/h	0,9		
Energy consumption for double pipe appliances (1) heating function	QDD	kWh/h	0,8		
Supply voltage		V-F-Hz	230-1-50		
Supply voltage minimum/maximum		V	198 / 264		
Maximum power consumption in cooling mode (1)		W	1200		
Maximum absorption in cooling mode (1)		A	5,4		
Maximum power consumption in heating mode (1)		W	1080		
Maximum absorption in heating mode (1)		A	4,8		
Dehumidification capacity		l/h	1,1		
Air flow rate in cooling environment (max/med/min)		m³/h	490 / 430 / 360		
Air flow rate in heating environment (max/med/min)		m³/h	450 / 400 / 330		
External air flow rate in cooling (max/min)		m³/h	500 / 370 / 340		
External air flow rate in heating (max/min)		m³/h	500 / 370 / 340		
Internal ventilation speed			3		
External ventilation speed			3		
Diameter wall holes		mm	202*		
Dimensions (Larg. x Alt. x Prof.) (without packaging)		mm	902 x 516 x 229		
Weight (without packaging)		Kg	40,5		
Sound pressure level (only internal) (EN 12102)	LWA	dB(A)	57		
Sound pressure (2)		dB(A)	🔊 33-42		
Degree of protection provided by covers			IP 20		
Refrigerant gas*		Type	R410A		
Global warming potential	GWP	kgCO2 eq.	2088		
Refrigerant gas charge		kg	0,85		
Power cable (N° pole x section mm²)			3 x 1,5		

LIMITS OF OPERATING CONDITIONS

Indoor Ambient Temperature	Maximum temperature in cooling	DB 35°C - WB 24°C
	Minimum temperature in cooling	DB 18°C
	Maximum temperature in heating	DB 27°C
	Minimum temperature in heating	-
Outdoor Ambient Temperature	Maximum temperature in cooling	DB 43°C - WB 32°C
	Minimum temperature in cooling	DB -10°C
	Maximum temperature in heating	DB 24°C - WB 18°C
	Minimum temperature in heating	DB -15°C

Performance and optimal operation are guaranteed with units operating alternately. In simultaneous operation ambient air fan speed works at minimum speed. Performance is measured by gas piping at a length of 5 m.

(1) TEST CONDITIONS: data refers to regulation EN14511

(2): Data test declaration in semianechoic room at a distance of 2m, minimum sound pressure with ventilation only. - By maintaining the same center to center distance of inlet and outlet holes and the possibility of installation with 162 mm diameter holes, models in the Unico Smart, Unico Inverter and Unico Act range may easily substitute previously installed Unico Star and Unico Sky models.

* hermetically sealed equipment containing fluorinated gas with GWP equivalent 2088

				UNICO TWIN WALL	
Product code				01274	
Nominal cooling capacity (1)		KW	❄️ 2,5		
Nominal heating capacity (1)		KW	🔥 2,2		
Nominal power consumption for cooling (1)		KW	0,9		
Nominal absorption for cooling (1)		A	4,2		
Nominal power consumption for heating (1)		KW	0,7		
Nominal absorption for heating (1)		A	3,2		
Maximum power consumption in cooling mode (1)		W	1200		
Maximum absorption in cooling mode (1)		A	5,4		
Maximum power consumption in heating mode (1)		W	1080		
Maximum absorption in heating mode (1)		A	4,8		
Dehumidification capacity		l/h	1,0		
Air flow rate in cooling environment (max/med/min)		m³/h	450 / 400 / 340		
Air flow rate in heating environment (max/med/min)		m³/h	450 / 400 / 340		
Internal ventilation speed			3		
Dimensions (Larg. x Alt. x Prof.) (without packaging)		mm	760 x 253 x 190		
Weight (without packaging)		Kg	8		
Sound pressure level (only internal) (EN 12102)		dB(A)	53		
Sound pressure (2)		dB(A)	🔊 27-38		
Degree of protection provided by covers			IP X1		
Power cable (N° pole x section mm²)			3 x 1		
Connecting liquid pipeline diameter	inch - mm		1/4 - 6,35		
Connecting gas pipeline diameter	inch - mm		3/8 - 9,52		
Maximum piping length	m		10		
Maximum height difference	m		5		

Easy installation



MASTER UNIT

Thanks to the template included in the package, the MASTER unit is installed, completely from the inside and in a few minutes, with the two holes of 202 mm diameter in the first room to be air conditioned.



The MASTER unit is connected to the WALL unit, thanks to the gas connection on the right side of the unit. Maximum length refrigerant lines: 10 meters.



WALL UNIT

The WALL unit is installed on the wall of the second room to be air conditioned.