



Characteristics





- Compact and low profile air only recessed air curtain, with full grille view, specially designed for applications without heating.
- Self-supporting casing construction made of galvanized steel plate, ready to be installed recessed in a false ceiling.
- Inlet grille (free of maintenance) made with aluminium profiles and blow-out nozzle, integrated in a single white frame colour RAL 9016. Other colours are available on request.
- Anodized aluminium outlet vanes, airfoil shaped, adjustable in both directions.
- Double-inlet centrifugal fans driven by an external rotor motor and low noise level. 5-speed selector. "EC" models assembled with very low consumption efficiency fans.
- Includes Plug&Play control with 7m RJ45 cable and infrared remote control. Optional: Clever control (programmable, automatic, intelligent, energy saving, Modbus RTU for BMS...).

Specifications

AIR ONLY

Model	Airflow m³/h	Power Fans 230V-50Hz kW	Current Fans 230V-50Hz A	Noise Level (5 m) dB(A)	Weight kg
RC M 1000 A	1800	0,212	0,94	55	33
RC M 1500 A	2700	0,318	1,41	56	50
RC M 2000 A	3600	0,424	1,88	57	61
RC M 2500 A	4500	0,530	2,35	58	68
RC ECM 1000 A	1840	0,132	1,14	56	33
RC ECM 1500 A	2760	0,198	1,71	57	50
RC ECM 2000 A	3680	0,264	2,28	58	61
RC ECM 2500 A	4600	0,330	2,85	59	68
RC G 1000 A	2400	0,642	2,85	57	37
RC G 1500 A	3200	0,856	3,80	58	55
RC G 2000 A	4800	1,284	5,70	59	71
RC G 2500 A	5600	1,498	6,65	60	78
RC ECG 1000 A	2700	0,225	1,95	61	37
RC ECG 1500 A	3600	0,300	2,60	62	56
RC ECG 2000 A	5400	0,450	3,90	63	71
RC ECG 2500 A	6300	0,525	4,55	64	78

Dimensions



L	L1	A	B
1000	1048	920	-
1500	1548	1420	710
2000	2048	1920	960
2500	2548	2420	1210

